

COSC-171: Computer Systems  
Fall 2021  
SAMPLE MID-TERM EXAM

1. **Provide short answers** to each of the following questions:
  - (a) What is stored in each *frame* on the *call stack*? Indicate, for each item, whether it is stored there by the *caller* or the *callee*.
  - (b) What are *internal and external fragmentation*? Which does a *segregated fits* allocator exhibit?
2. **Write a function** in x86-64 assembly code that *reverses the elements in an array* of integers. The parameters of this function are:
  - **rdi**: The address at which the array of 64-bit integers begins.
  - **rsi**: The length of the array, given as a number of integer entries.

The array should be reversed *in-place*—that is, the array to which **rdi** points should contain the result of the reversal. Here is a beginning to the function, which calculates, in **r10**, the address of the last entry in the array. **Complete this function.**

`reverse_array:`

```
;; Calculate the address of the final element.
mov  r9,  rsi ; last_offset = length ...
dec  r9      ; last_offset = (length - 1) ...
imul r9,  8  ; last_offset = (length - 1) * sizeof(int)
mov  r10, rdi ; last_addr = base ...
add  r10, r9 ; last_addr = base + offset

;; Perform the reversal...
```

3. Consider a garbage collected heap that occupies addresses `0x10000` through `0x90000`. Furthermore, assume that this heap is managed by a *semi-space GC*,

with the space divided at the halfway point, 0x50000. The lower address range is the *from-space*, and the higher address range is the *to-space*.

At the moment that the collector is triggered, there are a pair of objects in the *from-space*, one at 0x10200, the other at 0x12300, each of which contains a pointer to the other. There is a single pointer to the first object from the root set.

**Describe the actions of the semi-space GC on these two objects.** That is, when the root pointer to 0x10200 is followed, detail how the GC will act on these two objects, leaving them in the *to-space* and correctly pointing to one another. Choose addresses within the *to-space* to which the objects move, and show how the pointers are correctly updated.

4. Recall the four memory regions of a process: *text/code*; *statics*; *heap*; *stack*.

Answer the following questions about these regions:

- (a) Where does each appear in the virtual address space?
- (b) What is stored in each?
- (c) How is each created and managed? That is, what part(s) of the program and/or the system are responsible for each region?